



## RUBINETTO ALTO ELETTRONICO AD AZIONAMENTO A SENSORE CON REGOLAZIONE ACQUA CALDO/FREDDO TRAMITE DUE RUBINETTI SOTTOLAVABO CON FILTRO

Electronic high tap with sensor control, for pre-mixed water equipped with two angle valves with filter

D0SE17IL/99      cm  
30,3



Cromo

99

### testo di capitolato:

rubinetto alto elettronico cromato ad azionamento a sensore con regolazione acqua caldo/freddo tramite due rubinetti sottolavabo con filtro. con aeratore M24 ultrapiatto per installazione e rimozione con chiave apposita fornita. alimentazione con 4 batterie da 1,5V tipo AA al litio incluse. pressione di lavoro 1-6 bar. temperatura acqua max 65°C. ingressi G1/2" M. raggio d'azione predisposto 10 cm. portabatterie IPX5. connessioni IPX5. Elettronica omologata CE. dimensioni mm. 303x180x50. Goman Tipo codice D0SE17IL/99

### specifications:

High chromed electronic sensor operated faucet with hot/cold water adjustment by means of two angle valves with filter. with ultra-flat M24 aerator for installation and removal with special key supplied. power supply with 4 1.5V type AA lithium batteries included. working pressure 1-6 bar. water temperature max 65°C. G1/2" M inputs. range of action arranged 10 cm. IPX5 battery holder. IPX5 connections. CE approved electronics. dimensions mm. 303x180x50. Goman Type code D0SE17IL/99

