



## RUBINETTO ELETTRONICO AD AZIONAMENTO A SENSORE CON REGOLAZIONE ACQUA CALDO/FREDDO TRAMITE DUE RUBINETTI SOTTOLAVABO CON FILTRO

Electronic tap with sensor control, for pre-mixed water equipped with two angle valves with filter

D0SE17/99      30,3 cm



chromo

99

testo di capitolato:

rubinetto elettronico cromato ad azionamento a sensore con regolazione acqua caldo/freddo tramite due rubinetti sottolavabo con filtro. con aeratore M24. alimentazione con 4 batterie da 1,5V tipo AA al litio incluse. pressione di lavoro 1-6 bar. temperatura acqua max 80°C. ingressi G1/2" M. raggio d'azione predisposto 10 cm. portabatterie IPX5. connessioni IPX5. Elettronica omologata CE.

dimensioni mm. 153x170x50.  
Goman-Tipo codice D0SE17/99

specifications:

chromed electronic sensor operated faucet with hot/cold water adjustment by means of two angle valves with filter. with M24 aerator. power supply with 4x1.5V type AA lithium batteries included. working pressure 1-6 bar. water temperature max 80°C. G1/2" M inputs. range of action arranged 10 cm. IPX5 battery holder. IPX5 connections. CE approved electronics. dimensions mm. 153x170x50.  
Goman Type code D0SE17/99

